



C2G's Superbooster 4-Port USB over Cat6a Extender Kit – USB 3.2 Gen 1 (5Gbps) was designed to extend data from USB 3.2, 2.0 and 1.1 devices simultaneously up to 328 feet (100m) over a single Cat6a F/FTP cable, making it a perfect solution for USB 3.2 conferencing cameras, interactive white boards, security and monitoring, remote storage, and/or any other USB 3, 2 and 1 device.



No software drivers are required, making installation quick and easy with true plug and play convenience. Simply connect the Transmitter to the source computer, extend with a single category cable, and connect the Receiver to as many as four USB devices.

This Superbooster 4-Port Extender Kit provides the ability to connect USB 3.2 Gen 1 (5 Gbps) device types and is backwards compatible to USB 2.0 and 1.1 across a point-to-point connection.

Tested and Proven

This C2G Superbooster USB Extender has undergone rigorous compatibility testing with industry-leading video conferencing cameras, as well as solid state drives, docks, keyboards, mice and flash drives – ensuring total reliability and deployment confidence, plus saving valuable time for AV integrators as well.

Features & Benefits

- Extension of USB 3.2 data up to 328 ft (100m) over Cat6a cable
- USB 3.2 connectivity with data transfer rate up to 5Gbps
- Backwards compatible with USB 2.0 and 1.1
- Supports RS-232 pass-through and FSYNCGPIO pass-through (for industry camera use)
- Supports bi-directional 24V PoC
- Plug and play - no drivers required
- Perfect for extending cameras, white boards, storage drives, and other high bandwidth USB devices

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120542650	Country Of Origin	China
Features	Plug and Play	Application Sector	Commercial, Residential

Warranty Type	5-Year	Type	Active Device, Extender, Kit
---------------	--------	------	------------------------------

Dimensions

Product Width US	3.35 in	Product Depth US	3.94 in
Product Height US	1.0 in	Product Length US	3.35 in

Listing Agencies / 3rd Party Agencies

CE Certified	Yes	FCC Compliant	Yes
REACH Compliant	Yes		

Trade Programs

TAA Compliant	Yes		
---------------	-----	--	--

Additional Information

RoHS Compliant	Yes		
----------------	-----	--	--

Technical Information

Max Distance Support	328 ft	Storage Humidity	20-90% RH (Non-Condensing)
Technology Specifications	USB 1.1, USB 2.0, USB 3.2	Amperage	1 A
Data Transfer Rate	5 Gbps	Connector 2	RJ-45 Female, USB-A Female
Connector 1	RJ-45 Female, USB-B Female	Operating Temperature	0°-40°C, 32°-104°F
Operating Humidity	20-90% RH (Non-Condensing)	Storage Temperature	-31° - 140° C, -35° - 60° C
