



- ATX 3.1 ready, native dual-color PCIe CEM 5.1 connector
- Supports NVIDIA® GeForce RTX™ 40 series graphics cards
- Fully modular design, flat cables
- 80 PLUS Gold certified for high efficiency
- Active PFC design
- Protection with OVP / OCP / OPP / OTP / SCP / UVP
- 135 mm fluid dynamic bearing fan
- LLC half bridge topology with DC-to-DC module design

SPECIFICATIONS

Efficiency Rating	80 PLUS Gold (up to 90%)
Modular	Yes (fully modular)
Fan Size	135 mm
Fan Bearing	Fluid Dynamic Bearing
Dimensions (DxWxH)	150 x 150 x 86 mm
PFC Type	Active PFC
Input Voltage Range	100-240V~
Power Watt	1000W
Power Excursion	2000W (*up to 200% of the PSU's rated power for 100µs)
Input Frequency Range	50-60Hz
Protection	OCP / OVP / OPP / OTP / SCP / UVP
ATX (24 pin)	1
EPS (4+4 pin)	2
PCI-E 5.1 (16 pin)	1 (600W)
PCI-E (6+2 pin)	4
SATA (15 pin)	12
PERIPHERAL (4 pin)	4
FDD (4 pin)	1